

DATASHEET

# **Chicago Metallic™ L- and C-profiles**






## **Corrosion Resistant**



# Chicago Metallic™ L- and C-profiles Corrosion Resistant


- Visible sides adapted to the variety of grid widths
- Available in corrosion class D

## Assortment

Product group		Component description	Length (mm)	Colour	Pcs per pack	Lm per pack	Kg per pack
Wall angle options							
L19x24 C		L-wall angle 24x19 mm ECR Class C	3050	001	40	122	23
L24x24 C		L-wall angle 24x24 mm ECR Class C	3050	001	40	122	27
L19x24 D		L-wall angle 24 x 19mm ECR Class D	3050	001	40	122	23
L24x24 D		L-wall angle 24x24 mm ECR Class D	3050	001	20	61	13.8
C37 D		C-wall angle 20x40x20 mm ECR Class D	3050	001	32	97.6	32.5


## Product description

L19x24 C




- Body Material thickness 0.5mm

L24x24 C



- Body Material thickness 0.5mm


L19x24 D



- Body Material thickness 0.5mm


## Product description

L24x24 D



- Body Material thickness 0.5mm

C37 D



- Body Material thickness 0.5mm

## Performance



Reaction to fire

A1



Environment

Fully Recyclable

06.2024 | All colour codes mentioned are based on the NCS - Natural Colour System® property of and used on license from NCS Colour AB, Stockholm 2012 or the RAL colour standard. Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

# Sounds Beautiful

