

DATASHEET

# Chicago Metallic<sup>™</sup> T15 Hook 2750




**Sounds Beautiful**

# Chicago Metallic™ T15 Hook 2750

- 15 mm grid with a universal main runner and butt-cut cross tees
- Fully 38 mm high for better load bearing and compatibility with accessories
- A strong and stable grid which can be easily demounted repeatedly
- Used for creating more discreet grid lines in the ceiling finish

## Cross-section



## Compatible tiles

Semi-concealed




Exposed



## Coupling

Butt-cut end



## Assortment

Product group		Component description	Height (mm)	Length (mm)	Colour	Pcs per pack	Lm per pack	Kg per pack
<b>Main runner</b>								
T15 MR CL&HK		Main runner T15 Click / Hook	38	2700	001, 901	30	81	25.5
T15 MR CL&HK			38	3600	Color-All, 04, 88B, 11W, 001, 901	15	54	17.1
<b>Cross tee</b>								
T15 CT HOOK		Cross tee T15 Hook	38	1200	04, 88B, 11W, 001, 901	45	54	13.7
T15 CT HOOK			38	1350	04, 88B, 001, 901	30	40.5	10.5
T15 CT HOOK			38	600	04, 88B, 11W, 001, 901	45	27	7.1
T15 CT HOOK			38	675	04, 88B, 001, 901	75	50.63	13
T15 CT HOOK			38	1800	001	30	54	20.8
<b>Wall angle options</b>								
L19x24		L-wall angle 24x19 mm colour	24	3050	Color-All, 04, 88B, 11W, 901	40	122	23
W8x12		W-profile 15x12x8x15 mm	15	3050	Color-All, 04, 88B, 11W, 001, 901	30	91.5	17.9
W10x15		W-profile 15x15x10x15 mm	15	3050	Color-All, 04, 88B, 11W, 001, 901	30	91.5	19.9
<b>Accessories</b>								
FH B		Special hanger (bent) for Chicago Metallic™ T-profiles	57.5			100		1.5
QH HH 320		Assembled quick hanger with 2 hooks				100		5
HDC 1		Plastic hold down clip for tile thickness 15-20 mm (A edge), 15-30 mm (E edge), 20-25 mm (X, M, Z edge), 20-30 mm (D edge)				100		1.34
TR M6		Threaded rod M6 / L=1000 mm		1000		100		16.7
NUT M6		Nut M6				100		0.2
SS M6		Spacer sleeve M6				100		0.8
FC M6		Universal fixation clip / L=90 mm		90		100		1.5

Contact Rockfon® for the full range of wall angles and accessories.



## Position of slots and suspension holes

Product group	Component description	Height (mm)	Length (mm)	Slots	Distance between slots (mm)
T15 MR CL&HK	Main runner T15 Click / Hook	38	2700	16	84,375 / 168,75 / 14 x 168,75 / 84,375
T15 MR CL&HK		38	3600	36	50 / 100 / 34 x 100 / 50
T15 CT HOOK	Cross tee T15 Hook	38	1200	3	300 / 300 / 300 / 300
T15 CT HOOK		38	1350	1	675 / 675
T15 CT HOOK		38	600	1	300 / 300
T15 CT HOOK		38	675	1	337,5 / 337,5
T15 CT HOOK		38	1800	5	300 / 300 / 3 x 300 / 300
T15 CT HOOK		38	1800	5	

## Performance



### Load bearing capacity

Hanger distance (mm)	Module size (mm)	Kg/m <sup>2</sup>	
		Maximum deflection 2.5 mm	Maximum deflection 4.0 mm
1200	600 x 600	8.1	13.5
1200	1200 x 600	8.9	14.7



### Reaction to fire

A1



### Corrosion resistance

B



### Environment

Fully Recyclable

# Sounds Beautiful

