

DATASHEET

Chicago Metallic[™] T35 Hook 650




Sounds Beautiful

Chicago Metallic™ T35 Hook 650

- 35 mm grid with a knuckle-joint main runner coupling and butt-cut cross tees
- Fully 38 mm high for better load bearing and compatibility with accessories
- A strong and equal grid which can be easily demounted repeatedly
- Fire resistant grid according to national and European requirements
- Used for creating industrial ceilings with large sized and heavy panels
- System can be combined with 75 mm double height system

Cross-section




Compatible tiles



Coupling

Butt-cut end



Assortment

Product group		Component description	Height (mm)	Length (mm)	Colour	Pcs per pack	Lm per pack	Kg per pack
Main runner								
T35 MR HOOK		Main runner T35 Hook	38	3200	04, 00, 88B, 001	15	48	20.2
T35 MR HOOK			38	3600	04, 00, 88B, 001	15	54	22.8
Cross tee								
T35 CT HOOK		Cross tee T35 Hook	38	1500	04, 00, 88B, 001	40	60	24.5
T35 CT HOOK			38	1506.25	04, 00, 88B, 001	40	60.25	24.6
T35 CT HOOK			38	1995	04, 00, 88B, 001	15	29.93	12.7
T35 CT HOOK			38	600	04, 00, 88B, 001	50	30	12.3
T35 CT HOOK			38	1000	04, 00, 88B, 001	40	40	16.3
T35 CT HOOK			38	1200	04, 00, 88B, 001	40	48	19.6
Wall angle options								
L30x30		L-wall angle 30x30 mm	30	3050	001	25	76.25	23.3
Accessories								
FH B		Special hanger (bent) for Chicago Metallic™ T-profiles	57.5			100		1.5
HDC 6 P2		Steel hold down spring combinable with holddown clip HDC 6 P1				100		2.7
HDC 6 P1		Steel hold down clip for tile thickness 45-110 mm (A edge) (to be combined with HDC 6 P2)				100		0.9
QH HH 140		Assembled quick hanger with 2 hooks				100		3.6

Contact Rockfon® for the full range of wall angles and accessories.



Position of slots and suspension holes

Product group	Component description	Height (mm)	Length (mm)	Slots	Distance between slots (mm)
T35 MR HOOK	Main runner T35 Hook	38	3200	32	
T35 MR HOOK		38	3600	18	
T35 CT HOOK	Cross tee T35 Hook	38	1500	0	
T35 CT HOOK		38	1506.25	0	
T35 CT HOOK		38	1995	0	
T35 CT HOOK		38	600	1	
T35 CT HOOK		38	1000	1	
T35 CT HOOK		38	1200	1	
T35 CT HOOK		38	1200	1	

Performance



Load bearing capacity

Hanger distance (mm)	Module size (mm)	Kg/m ²	
		2.5 mm	4.0 mm
1200	600 x 600	11.8	19.9
1200	1200 x 600	13.0	21.5
1200	1500 x 1000	4.7	7.9
1500	1500 x 1000	3.2	5.6



Reaction to fire

A1 / A2-s1,d0 (Color-all)



Corrosion resistance

B



Environment

Fully Recyclable

06.2024 | All colour codes mentioned are based on the NCS - Natural Colour System® property of and used on license from NCS Colour AB, Stockholm 2012 or the RAL colour standard. Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

Sounds Beautiful

