

DATASHEET

Chicago Metallic™ W-profiles



Chicago Metallic™ W-profiles

- A range of W profiles (shadow moulding wall angles) for various applications
- Designed for Rockfon tiles (A, E, D, M, X, & Z-edge)
- Specific corner caps available

Assortment

Product group		Component description	Length (mm)	Colour	Pcs per pack	Lm per pack	Kg per pack
Wall angle options							
W8x12	TATION OF THE SALES	W-profile 15x12x8x15 mm	3050	Color-All, 04, 88B, 11W, 001, 901	30	91.5	17.9
W10x15	The last self-self MMZ of	W-profile 15x15x10x15 mm	3050	Color-All, 04, 88B, 11W, 001, 901	30	91.5	19.9
W20		W-profile 20x20x20x20 mm	3050	04, 88B, 001, 901	20	61	27.8
W20x20x20x30		W-profile 20x20x20x30 mm	3050	001	18	54.9	28.1
Accessories							
CC 15 OUT		Outside flat corner for W-profile flange 15 mm		11W, 001	50		0.85
CC 15 IN		Inside flat corner for W-profile flange 15 mm		11W, 001	50		0.8


Product description

W8x12

- W-profile with 15 mm face and mounting surface.
Suitable for semi-concealed and concealed panels of 12 mm and 8 mm. (D and E edge tiles)
Rockfon tile labelling on the inside.

Body Material thickness0.5mm

W10x15



 W-profile with 15 mm face and mounting surface.
 Suitable for semi-concealed and concealed panels of 10 mm and 15 mm. (E, M, X and Z edge tiles)
 Rockfon tile labelling on the inside.

Body Material thickness0.5mm

Product description

W20




- Reinforced W-profile with a 20 mm face.

Used in self-supporting corridor constructions.

Also ideal for the fixation of light removable partitions thanks to the possibility for larger suspension distances.

Body Material thickness0.7mm

W20x20x20x30



- Reinforced W-profile with a 30 mm face.

Used in seismic constructions. Also ideal for the fixation of light removable partitions thanks to the possibility for larger suspension distances.

Body Material thickness0.7mm

Performance



Reaction to fire

A1 / A2-s1,d0 (Color-all)



Sounds Beautiful