

DATASHEET

# Chicago Metallic T24 Hook 2850




**Sounds Beautiful**


# Chicago Metallic T24 Hook 2850

- 24mm grid with universal main runner and butt-cut cross tee connections
- 38mm high components for better load bearing and compatibility with accessories
- A strong and stable grid which can be easily demounted time and again
- Used to create concealed, semi-concealed and exposed ceiling solutions

## Cross-section




## Compatible tiles



## Coupling

Butt-cut end



## Assortment

Product group		Component description	Height (mm)	Length (mm)	Colour	Pcs per pack	Lm per pack	Kg per pack
<b>Main runner</b>								
T24 MR CL&HK		Main runner T24 Click / Hook	38	3600		15	54	19.5
T24 MR CL&HK			38	2400	001	25	60	21.3
T24 MR CL&HK			38	4050	11, 001, 901	25	101.25	36
<b>Cross tee</b>								
T24 CT HOOK		Cross tee T24 Hook	38	300	04, 88, 001, 901	150	45	13.1
T24 CT HOOK			38	675	001, 901	75	50.63	14.7
T24 CT HOOK			38	600	04, 88, 11, 001, 901	45	27	8.2
T24 CT HOOK			38	1350	001, 901	50	67.5	19.6
T24 CT HOOK			38	1200	04, 88, 11, 001, 901	45	54	15.7
T24 CT HOOK			38	1500	04, 88, 001, 901	50	75	26.4
T24 CT HOOK			38	1800	04, 88, 11, 001, 901	25	45	16.2
<b>Wall angle options</b>								
W8x12		W-profile 15x12x8x15 mm	15	3050	Color-All, 04, 88, 001, 901, 11	30	91.5	17.9
W10x15		W-profile 15x15x10x15 mm	15	3050	Color-All, 04, 88, 001, 901, 11	30	91.5	19.9
L19x24		L-wall angle 24x19 mm colour	24	3050	Color-All, 04, 88, 901, 11	40	122	23
<b>Accessories</b>								
FH B		Special hanger (bent) for Chicago Metallic™ T-profiles	57.5			100		1.5
QH HH 320		Assembled quick hanger with 2 hooks				100		5
HDC 1		Plastic hold down clip for tile thickness 15-20 mm (A edge), 15-30 mm (E edge), 20-25 mm (X, M, Z edge), 20-30 mm (D edge)				100		1.34
TR M6		Threaded rod M6 / L=1000 mm		1000		100		16.7
NUT M6		Nut M6				100		0.2
SS M6		Spacer sleeve M6				100		0.8
FC M6		Universal fixation clip / L=90 mm		90		100		1.5

Contact Rockfon® for the full range of wall angles and accessories.

Please note that not all colors are available for every product. We recommend checking the assortment table for the colors currently offered for each item. If you need further assistance or have specific color preferences, please feel free to contact Rockfon.



## Position of slots and suspension holes

Product group	Component description	Height (mm)	Length (mm)	Slots	Distance between slots (mm)
T24 MR CL&HK	Main runner T24 Click / Hook	38	3600	36	50 / 100 / 34 x 100 / 50
T24 MR CL&HK		38	2400	24	50 / 100 / 22 x 100 / 50
T24 MR CL&HK		38	4050	24	84,375 / 168,75 / 22 x 168,75 / 84,375
T24 CT HOOK	Cross tee T24 Hook	38	300	0	300
T24 CT HOOK		38	675	1	337,5 / 337,5
T24 CT HOOK		38	600	1	300 / 300
T24 CT HOOK		38	1350	1	675 / 675
T24 CT HOOK		38	1200	3	300 / 300 / 300 / 300
T24 CT HOOK		38	1500	0	1500
T24 CT HOOK		38	1800	5	300 / 300 / 3 x 300 / 300

## Performance



### Load bearing capacity

Hanger distance (mm)	Module size (mm)	Kg/m <sup>2</sup>	
		2.5 mm	4.0 mm
1200	600 x 600	9.9	16.5
1200	1200 x 600	10.9	17.9
1200	1800 x 600	3.3	5.7
1200	675 x 675	6.4	10.8
1200	1350 x 675	7.2	11.9
1350	675 x 675	5.2	8.8
1350	1350 x 675	5.8	9.7



### Reaction to fire

A1 / A2-s1,d0 (Color-all)



### Corrosion resistance

B



### Environment

Fully Recyclable

# Understanding the performance of Chicago Metallic grids and accessories



## Reaction to fire

Reaction to fire is classified in accordance with EN 13501-1. Chicago Metallic steel grids and accessories are non-combustible.



## Fire resistance

A range of Chicago Metallic steel grids are tested in combination with different Rockfon tiles and are classified in accordance with European norm EN 13501-2 and/or national norms.



## Colours

Chicago Metallic grids are available in various colours from the RAL and NCS systems, which are measured following the ISO 7724-2 and ISO 7724-3 standards. The actual colours may deviate slightly from the RAL and NCS references. Chicago Metallic grids are available in a variety of finishes from matt to high gloss, with a respective average of < 5, 15 and 50 units at a 60° angle. The matt finishing is measured at an angle of 85°. See the colour legend for their average values. The gloss unit is measured in accordance with EN13523 part 2.



## Corrosion resistance

Chicago Metallic products produced from hot dip galvanised steel following the Sendzimir process comply with the corrosion classes of the product standard EN 13964 (A, B, C, D). The standard systems in class B are protected with 100 g/m<sup>2</sup> zinc evenly applied on both sides. The enhanced corrosion resistance (ECR) systems and accessories in class C or D have respectively a layer of 100 g/m<sup>2</sup> and 275 g/m<sup>2</sup> zinc evenly applied on both sides and are protected with an additional layer of 20 micron paint per side.



## Load bearing performance

The load bearing performance (max. kg/m<sup>2</sup> load applicable to the grid system without exceeding the allowable deflection of the individual components) is tested in accordance with the EN 13964 standard. The accumulative value of the system deflection, shown on the data sheets, does not exceed the max. deflection as given in class 1 of the standard. Special project configurations deviating from the standard module sizes mentioned in the data sheets must be calculated by Rockfon technical services.



## Cleaning

All Chicago Metallic grids can be cleaned with water and a mild detergent in combination with a melamine foam sponge or microfiber cloth.

## Colour legend

Please note that not all colors are available for every product. We recommend checking the assortment table for the colors currently offered for each item. If you need further assistance or have specific color preferences, please feel free to contact Rockfon.

White 001 RAL 9003	White 901 RAL 9010	White 01 White 916	Matt White 11 RAL 9003	L value: 93 Gloss: 2 at both a 60° and 85° angle
Platinum 54 RAL 7035	Alugrey 04 RAL 9006	Galvanised 00 Galvanised 69	Matt Black 88 RAL 9004	Gloss: 4.5 at 60° angle and 11.5 at 85° angle
Brushed Alu 534	High Gloss Chrome 14	Carrara 57	High Gloss Brass 16	
White 001 / White 001 (8WW) RAL 9003 / RAL 9003	Black 08 / Black 08 (8BB) RAL 9005 / RAL 9005	White 001 / Black 08 (8WB) RAL 9003 / RAL 9005	Alugrey 04 / Black 08 (8GB) RAL 9006 / RAL 9005	

# Rockfon Color-all®

Mustard - 51 NCS S 2050-Y20R	Sand - 30 NCS S 1020-Y30R	Stucco - 20 NCS S 1005-Y20R			
Scarlet - 71 NCS S 5040-Y90R	Coral - 76 NCS S 3040-Y90R	Seashell - 75 NCS S 1010-Y70R	Petal - 74 NCS S 1005-Y60R		
Seaweed - 34 NCS S 8005-G	Eucalyptus - 32 NCS S 6020-B90G	Sage - 31 NCS S 3010-G10Y	Mint - 12 NCS S 0505-G10Y		
Space - 49 NCS S 7020-B	Storm - 48 NCS S 5030-R90B**	Azure - 47 NCS S 3020-B	Fresh - 42 NCS S 2010-B10G		
Earth - 25 NCS S 5010-Y50R	Clay - 26 NCS S 5005-G50Y	Linen - 22 NCS S 4005-Y50R	Sandalwood - 13 NCS S 2010-Y70R	Chalk - 21 NCS S 2005-Y40R	
Ebony - 28 NCS S 8005-R	Cork - 24 NCS S 4010-Y30R	Hemp - 23 NCS S 3005-Y			
Iron - 18 NCS S 7502-B	Concrete - 06 NCS S 5502-B	Mastic - 17 NCS S 4000-N	Zinc - 05 NCS S 4005-R50B	Mercury - 62 NCS S 3005-R80B*	
Charcoal - 09 NCS S 8500-N	Anthracite - 08 NCS S 7005-B	Gravel - 03 NCS S 3502-B	Plaster - 02 NCS S 2005-R80B	Stone - 01 NCS S 2000-N	Moon - 10 NCS S 1005-R80B

\* Colour contains effect pigments.

\*\* Colour is between NCS S 5030-R90B and NCS S 6030-R90B.

Please note that not all colors are available for every product. We recommend checking the assortment table for the colors currently offered for each item. If you need further assistance or have specific color preferences, please feel free to contact Rockfon.

NCS codes are closest colour match. The actual colour of the Rockfon Color-all® grid may deviate slightly from printed colours due to the texture of the surface. Samples are available upon request.

# Sounds Beautiful

